

HI PRO 1000 is the ultimate 303 API Modified thread compound. This formulation is suitable for use on casing, tubing and line pipe. **HI PRO 1000** is manufactured in accordance with specifications set forth in API Bulletin 5A2 (1972).

HI PRO 1000 out-performs other API-Modified compounds due to its proprietary blend of greases which improves its thread-wetting ability

| Specific Characteristics (PER API 5A2) | |
|--|--------------|
| Grease | 36.0% +/-1.0 |
| Power Graphite | 18.0% +/-1.0 |
| Lead Powder | 30.5% +/-0.6 |
| Zinc Dust | 12.2% +/-0.6 |
| Copper Flake | 3.3% +/-0.6 |

| Typical Characteristics | |
|-------------------------|---------------|
| NLGI grade | 1 |
| ASTM Penetration | 310-340 |
| Texture | Buttery |
| Flashpoint | 460°F (237°C) |
| Color | Copper- Brown |
| Brushable to | 0°F (-18°C) |

| Component Specifications | | |
|--|--------------------|------------|
| Lead | 325 mesh 1% max. | 99.9% min. |
| Copper | 325 mesh 1% max. | 97.0% min. |
| Graphite | 200 mesh 0.5% max. | 99.5% min. |
| Corrosion, rust and oxidation inhibitors proprietary | | |

DO NOT USE ON OXYGEN LINES